Shri Caneshay Namah Shi Mahaviray Namah

## SAMIR TRADING CORPORATION

666, Room No: 5A, First Floor, Sheth Harilal HariVallabhdas Trust Building, Above Shree Gopal Elec Co., Nr Kothari Pole, Gandhi Road, Ahmedabad-380001. PH: 22170118, Mob: 9725399929, 9016813316

E-mail: samirtradingcorp@gmail.com Website: www.samirtrading.in

WE DEAL IN FULL RANGE OF CONTROL PANEL ACCESSORIES AND EVERYTHING IN ELECTRICALS

## STAINLESS STEEL CABLE TIES

Samir offers self locking (Ball lock & ladder type) cable ties in Stainless Steel (Grade 304 & 316) with smooth edges even safely install by hand.

Stainless Steel is suitable to use in hard condition like corrosive atmosphere, extreme temperature & offshore conditions.

Especially available with halogen free, Polyester/Nylon coating which is ideal to use in extreme low temperature and improves corrosion resistance.

These ties are available in 0.25 mm thickness, 4.6 & 7.9 mm width & 100 to 1000 mm length. Locking head dia of  $4.6 - 11.00 \times 6.50 \times 4.50$  mm &  $7.9 - 14.00 \times 10.60 \times 5.50$  mm.

- Ladder type (width 7mm & 12mm) & releaseable (width 6mm & 9mm) Cable ties are available in full range.
- Binding strap in required size with various types of buckles are available on request.

| TECHNICAL DATA: (BALL LOCK ONLY) |                                    |  |
|----------------------------------|------------------------------------|--|
| Material:                        | Stainless steel Grade 304 / 316    |  |
| Coating:                         | Polyester / Nylon                  |  |
| Minimum<br>tensile<br>strength:  | 4.6 mm width Un-coated (45 kg)     |  |
|                                  | 7.9 mm width Un-coated (113 kg)    |  |
|                                  | 4.6 mm width Coated (45 kg)        |  |
|                                  | 7.9 mm width Coated (113 kg)       |  |
| Operating temperature:           | Stainless Steel: - 80' to + 540' C |  |
|                                  | Polyester: - 40' to + 140' C       |  |
|                                  | Nylon: - 80' to + 150' C           |  |

| No. | Length (mm) | MAX. BUNDLE<br>DIA. (mm) |
|-----|-------------|--------------------------|
| 01  | 100         | 20                       |
| 02  | 150         | 35                       |
| 03  | 200         | 50                       |
| 04  | 250         | 60                       |
| 05  | 300         | 80                       |
| 06  | 360         | 100                      |
| 07  | 520         | 150                      |
| 80  | 680         | 200                      |
| 09  | 840         | 250                      |
| 10  | 1000        | 300                      |

## ■ Tensioning & Cutting tools are available.

Sizes & material grade could be changed as per requirements.













